


MAGIC 1500

HARDWARE DETAILS



Specifications

*POWER:	110V AC
*COOLING:	PASSIVE (SILENT)
*CONNECTIONS:	3 10/100 ETHERNET (2 ARE FOR PASS-THROUGH) 1 POWER CONNECTOR
*1 U RACKMOUNT DIMENSIONS:	1.75IN(H) x 17.1IN(W) x 6.8IN(D) 4.4CM(H) x 43.5CM(W) x 17.3CM(D)
*SMALL FORM FACTOR DIMENSIONS:	1.9IN(H) x 9.2IN(W) x 7.0IN(D) 4.9CM(H) x 23.4CM(W) x 17.7CM(D)

Connectivity

- *10/100 Ethernet Connectivity (can pass 2 other devices through the Magic 1500)
- *An IP address (Through DHCP or a static IP address for the Magic 1500)
- *Outbound (to the internet) http/HTTPS access (HTTP/HTTPS is user configurable)
- *Inbound (to the print devices) UDP 161 (SNMP) access
- *SNMP community string for all print devices
- *IP network ranges for your print devices (the Magic 1500 will auto-discover any print devices in the IP range)
- *The Magic 1500 only communicates with the network devices across UDP port 161. BY DESIGN IT WILL SCAN THE NETWORK RANGE PROVIDED BY THE CUSTOMER. THE CUSTOMER CAN PROVIDE INDIVIDUAL IP ADDRESSES, IP ADDRESS RANGES, SUBNETS OR ANY COMBINATION OF THESE. THE MAGIC 1500 CAN BE CONNECTED ANYWHERE ON THE NETWORK AS LONG AS IT HAS THE ABOVE CONNECTIVITY.

